



SPJ3E
PORTABLE EV CHARGER
3.5KW/7KW



Functional Features:

- Plug and Charge
- Scheduled Charging
- Adjustable Charging Current
- Built-in Smart Chip for Automatic Fault Repair

Design & User Interface Features

- Waterdrop-Inspired Design
- Display Screen & Status Indicators
- 2.8-inch LCD Display

Product Dimension Drawing (mm)



Specifications

ITEM	SPJ3E-3.5	SPJ3E-7
Power Supply	1P+N+PE	1P+N+PE
Rated Voltage	95-275V AC	95-275V AC
Rated Current	Max 16A(6/8/10/13/16A)(MAX)	Max 32A(10/16/20/24/32A)(MAX))
Frequency	50/60Hz	50/60Hz
Output Voltage	220-240V AC	220-240V AC
Maximum Current	13A/16A	32A
Rated Power	3.5 kw	7kw
Charging Port	Type 2 /Type 1 /GBT/NACS	
Cable Length	5/7/10 M Optional	
Cover Material	PC+Siloxane Alloy	
LED Indicator	Red/Blue/Green	
LED display	2.8" LCD Display	
Start Mode	Plug-in & Charge	
Residual Current Protection	Type A 30mA AC	
IP Degree	IP67	
Impact protection	IK08	
Multiple Protection	Over/Under Current Protection , Short Circuit Protection, Ground Protection , Surge Protection, Over/Under Voltage Protection, Over/Under Temperature Protection	
Certification	CE &UKCA	
Certification Standard	EN IEC 61851-1:2019; EN 62752:2016/A1:2020 , EN IEC 61851-21-2:2021; EN IEC 61000-6-1:2019 , EN IEC 61000-6-3:2021	
Warranty	2 Years	
Installation	Wall-Mounting (Column Optional)	
Work Temperature	-30℃~ 50℃	
Storage Temperature	-40℃~ 70℃	
Work Humidity	5% -95%RH	
Work Altitude	<2000M	

Plug Standard Selection



EU version



US version



UK version



GER version



GBT version